

Cleanroom Window Series

FLUSH CLEAN WINDOW



Product Features

- The window frame is made of aluminum alloy, and can be selected in black, white, or stainless steel.
- There are aluminum mounting slots around the frame. Depending on the type of wall panels on site, aluminum or aluminum troughs can be used to connect the wall panels, which is highly applicable.
- Special glass such as fireproof glass, frosted glass, and yellow light glass can be selected.
- The products are widely used in laboratories, pharmaceutical factories, clean corridors, and other places.

Parameter

Aluminum alloy frame thickness: 1.3mm
Tempered glass thickness: 5mm
Desiccant type: mineral desiccant

Product Features

- The window frame is made of aluminum alloy, and can be selected in black, self-colored, and stainless steel styles.
- The frame adopts a movable buckle edge structure with self-enclosed edging, and does not require a trough during installation, which is highly applicable.
- Special glass such as fireproof glass, frosted glass, and yellow light glass can be selected.
- The products are widely used in laboratories, pharmaceutical factories, clean corridors and other places.

Parameter

Aluminum alloy frame thickness: 1.1mm
Tempered glass thickness: 5mm
Desiccant type: mineral desiccant

CLAMPING CLEAN WINDOW



Product Features

- The window frame is made of aluminum alloy, and can be selected in black, white, or stainless steel.
- There are aluminum mounting slots around the frame. Depending on the type of wall panels on site, aluminum or aluminum horse can be used to connect the wall panels, which is highly applicable.
- Special glass such as fireproof glass, frosted glass, and yellow light glass can be selected.
- The electric-controlled atomized glass is used, and the atomized or transparent effect can be selected according to different scenes.
- The products are widely used in laboratories, pharmaceutical factories, clean corridors and other places.

Parameter

Technical parameters:
Aluminum alloy frame thickness: 1.3mm
Tempered glass thickness: 5mm
Desiccant type: mineral desiccant

FLUSH ELECTRONIC ATOMIZATION WINDOW



Before atomization



After atomization



Flush clean window



Flush clean window



Conventional clean window category

You can choose aluminum or aluminum horse to connect the wall panels, which is highly applicable



outer square inner circle window



Right angle window



Decheng kunling


FLUSH CLEAN WINDOW




CLAMPING CLEAN WINDOW



Flush clean windowConventional dimensions and installation method



使用铝马槽连接机制板
Using aluminum manger to connect machine panels



使用中字铝连接手工板
Using Chinese aluminum to connect handmade boards

Clamping clean windowConventional dimensions and installation methods

